

CLASSIC PC

Start-up range of Electric Airless Paint Sprayers for Professional Painting Contractors



PROFESSIONAL ADVANTAGES

- Ideal for small to medium family housing and light commercial projects
- Graco 'Big' technologies in a compact size
- Finish every job, every day thanks to ProConnect[™] fast pump replacement system



CLASSIC PC

Best Value in small electric sprayers!

FINISH EVERY JOB, EVERY DAY

The next generation of **CLASSIC** sprayers have now been upgraded with ProConnect[™]. This fast and easy on-the-job pump replacement system, makes the most reliable small electric units even more valuable.

The **390 CLASSIC PC** with brush motor is a solid workhorse built for professionals just "starting out". It's the ideal sprayer for residential jobs.

Proven Endurance[™] pump technology on all **CLASSIC** models, makes it perfect for professionals who frequently spray a wide range of interior coatings.

The **CLASSIC**^S **395**/**495** are the best choice for professionals looking for superior performance, control and extra comfort for daily use on residential jobs.

The **CLASSIC**^S feature the FTX^m-E gun, variable speed motor and SmartControl^m 1.0, with electronic control for a consistent spray pattern at every pressure.

All Hi-Boy **CLASSIC** models are configured with a multi-functional cart version, offering pneumatic wheels, direct suction, a kick back, hose wrap and a convenient toolbox as a premium.

Comfortable Carrying Offset handle with rubber comfort grip balances sprayer away from leg

CLASSIC



Swivel Inlet Suction Hose

- All aluminium construction is durable, lightweight and rust proof
- No-tools removal of hose for cleaning or
- accessing inlet ball
- Easily swivels to reach paint buckets or cans

CLASSIC

Frame

- Stands upright so it won't tip paint can over

- Attached big cup holds the inlet during transport to catch drips

Variable Pressure Control (only CLASSIC 390 models)

Position indicator allows repeatable setting while spraying light-to heavier materials

Watch our application videos at: tp://www.contractorclub.com

Materials & Applications

The CLASSIC has been tested and approved to spray a wide range of lacquers, acrylic, primers, enamels, varnishes and acrylic interior paints, <u>out of the bucket</u>.

The ideal unit for interior renovation of small residential and light commercial projects.



CLASSIC^S

Easy-Out[™] Pump Filter

- Large filtering area reduces tip clogs
- and ensures a quality finish - Inside out filter design filters won't collapse and cleans with
- only a few liters - Vertical filter design removes

CLASS

195

simply with the cap, eliminates spill





SmartControl[™] 1.0 With variable speed control delivers consistent spray pressure.

Features PRD CONNECT

Semi-Pneumatic Wheels - Roll easily over rough terrain

GOOD TO KNOW

EXTEND YOUR REACH!

JetRoller™ The ideal renovation tool

Extend your sprayer with the JetRoller and minimize application time when combining rolling and spraying into one operation. Uses commonly available 18 or 25 cm roller covers.

Benefits:

- Reduces overspray
- Eliminates reaching
- Eliminates climbing and continually reaching up and down - Complete large jobs in half the time of traditional methods

Kit includes a lightweight detachable roller frame, 50 cm extension, CleanShot[™] Shut-Off[™] valve, Inline[™] gun, spray tip and guard.

Hopper

A convenient 5.7 liter hopper, compatible with all units





With a spare pump ready,

TIP

you'll always be able to finish your job!



Hi-Boy Exclusive Features

PRD

- Thick chrome over steel to withstand rugged environments
- Retractable handle doubles as a hose wrap for simple removal of coiled hose
- Comfortable inlet suction allows direct suction out of up to 30 liter buckets
- TiltBack[™] easily allows one man bucket change and on board toolbox



Features CONNECT

Exchange your pump easily YOURSELF in 3 steps in case any damage appears.

No more time wasted or money lost to labour charges on pump repairs.



clamping nut



Open door and remove pump



Remove hose and suction tube



CLASSIC PC Accessories

Get the most out of your equipment, using our professional accessories

	ve your							
10	FTX™-E Gi	uns		JetRoller [™] System 0.5 m Heavy Duty Extension				
2 And	288438	0			with Inline™ Gu		without In	
		RAC X guard and 2 fi		1	24V490	roller 18 cm	24V492	roller 18 cm
1	262116	FTX [™] -E gun with RA(1		roller 25 cm	24V493	roller 25 cm
		60 mesh filter, no tip)		232123	1 m Heavy Dut	ty extension	
	Easy-Out [*]	™ Gun Filters			Hopper			
2200	257129	30 mesh, grey 🛛 28	37033 100 mesh, blue	A V	288526	5.7 liter / stand		
100	287032	60 mesh, black 25			24B250	5.7 liter / hi-bo	by version	
	Easv-Out	[™] Pump Filters			RAC X Tip Ex	ctensions		
	246425	30 mesh, grey		2222	287019	25 cm	287021	50 cm
3320	246384	60 mesh, black (= st	tandard)		287020	40 cm	287022	75 cm
00	246382	100 mesh, blue	,					
	246383	200 mesh, red				RAC X [™] Pole G		
					287026	90 cm	287027	180 cm
	BlueMax ^{**} 214698		41272 1/4" x 20 m		Dellare Evte	-ior (complete	-1	
	214698 240794		41272 1/4" x 20 m 23771 1/4" x 30 m		Rollers Exte 6880095	rior (complete 30 cm fixed	*)	
	240134	1/4 X 10 III • 22	3//1 1/4 X JU II		6880095 098084	30 cm fixed 90-180 cm tel	acconic	
	Hose Con	nectors			098085	45-90 cm teles		
	156971	1/4" x 1/4"		ST.	000000	40 00 0m tare	200010	
1999 (S)	157350	1/4" x 3/8"			Roller Kit			
					245397	Fixed interior r		
\frown	Whips (23			14		23 cm - Cover	12 mm - InLi	ine [™] gun
	238358	3/16" x 0.9 m		E				
	238359	3/16" x 1.8 m			Tips & Guard			
	238959	3/16" x 1.4 m			FFAXXX	Green RAC X fi		
	Dife ton Dr	Ocean at Dum			PAAXXX	Blue RAC X pro		
Team I	Blister Pa 17C489	Rister Pack fits all (WA12XX	RAC X WideRad	C, for Dly Sun	aces
	176405	Blister Pack, fits all C	JIASSIC PU		246215	RAC X guard		
	ProGuard	·**-		4	Liquids			
	24W090	230V, CEE 7/7, shuk	(0		206994	TSL [™] 0.25 I		
T	24W755	230V, IEC320, multic			253574	Pump Armor [™] 1	11	
necifi	cations				T T	7		T
					6			
I IINITS S	HIP complete	and ready to spray with: FTX™	M-E A-finger gun.		2			192
ers (gun + ma	anifold), 240794	4 BlueMax™ II hose 1/4" x 15m		The Astron	10 -			12 N V
; X™ (PAA517	7) tip and guard	1.			· 🕒 /	, T> 📟	70 1	
				CLASSIC 390 P		390 PC CLASSI		
				Stan	d I	Hi-Boy	Stand	Hi-I
	rs: for EUR(0 version (230 V)		17C34	<u>ع</u> ام	7C349	17C361	17E(
rt Number	101 11	icord version (230 V)		17034	-	70351	-	17E
rt Numbei	for Multi			17034		-	17C359	
	for UK (1	110 V)				' (3300)	227 (3300)	227 (33
ax. Working	for UK (1 g Pressure -	110 V) bar (PSI)		227 (3300		(0000)		
ax. Working ax. Fluid Flo	for UK (1 g Pressure - I low - I/min. (g	110 V) bar (PSI)		1.8 (0.47	7) 1.8	8 (0.47)	2.0 (0.54)	2.3 (0
ax. Working ax. Fluid Flo ax. Tip Size	for UK (1 g Pressure - low - I/min. (g e - 1 gun	110 V) bar (PSI)		1.8 (0.47 0.021	7) 1.8 "	8 (0.47) 0.021"	2.0 (0.54) 0.023"	0.0
ax. Working ax. Fluid Flo ax. Tip Size eight - kg (l	for UK (1 g Pressure - low - I/min. (g e - 1 gun (lbs)	110 V) bar (PSI)		1.8 (0.47 0.021 14 (30	7) 1.8 " D)	8 (0.47) 0.021" 14 (30)	2.0 (0.54) 0.023" 19 (42)	0.0 33
ax. Working ax. Fluid Flo ax. Tip Size eight - kg (l otor Rating	for UK (1 g Pressure - low - I/min. (g e - 1 gun (lbs) g - HP	110 V) bar (PSI) gpm)		1.8 (0.47 0.021 14 (30 5/8 D	7) 1.8 " D) C	8 (0.47) 0.021" 14 (30) 5/8 DC 7	2.0 (0.54) 0.023" 19 (42) 7/8 TEFC DC	0.0 33 1.0 TEF0
ax. Working ax. Fluid Flo ax. Tip Size eight - kg (l otor Rating	for UK (1 g Pressure - low - I/min. (g e - 1 gun (lbs)	110 V) bar (PSI) gpm)		1.8 (0.47 0.021 14 (30	7) 1.8 " D) C	8 (0.47) 0.021" 14 (30)	2.0 (0.54) 0.023" 19 (42)	0.0
ax. Working ax. Fluid Flo ax. Tip Size eight - kg (l otor Rating nimum Ger	for UK (1 g Pressure - low - I/min. (g e - 1 gun (lbs) g - HP	110 V) bar (PSI) gpm) uirement - W		1.8 (0.47 0.021 14 (30 5/8 D	7) 1.8 " D) C	8 (0.47) 0.021" 14 (30) 5/8 DC 7	2.0 (0.54) 0.023" 19 (42) 7/8 TEFC DC	0.0 33 1.0 TEFC
ax. Working ax. Fluid Flo ax. Tip Size eight - kg (l otor Rating inimum Ger atures: Til To	for UK (1 g Pressure -) low - l/min. (g e - 1 gun (lbs) g - HP enerator Requ	110 V) bar (PSI) gpm) uirement - W icket Hook		1.8 (0.47 0.021 14 (30 5/8 D	7) 1.8 " 0) C 0 -	8 (0.47) 0.021" 14 (30) 5/8 DC 7 4000	2.0 (0.54) 0.023" 19 (42) 7/8 TEFC DC	0.0 33 1.0 TEFC 4

Stavanger Korrosjon AS

Strandbakken 3 • 4070 Randaberg • Norway • Tel: +47 51410711 E-mail: post@stavanger-korrosjon.no • http://www.stavanger-korrosjon.no

© 2015 Graco BVBA · Form No. 300733ENEU (rev.A) · 07/15 · Printed in Europe. Graco is certified ISO 9001. All information, illustrations, and specifications in this document are based on the latest product

information available at the time of publication. The right is reserved to make changes at any time without notice.